

FloPlast PVC-U Rainwater Systems

Rainwater Systems Compatibility Chart

	Xtraflo 170mm	Niagara Ogee	Hi-Cap	Half Round 112mm	Square Line	MiniFlo
Manufacturer						
Hepworth	✗ (No equivalent)	✓ (Ogee)	✓ (High capacity)	✓ (Clickfit)	✓ (Clickfit)	✗ (Clickfit)
Brett Martin	✗ (No equivalent)	✗ (Prostyle)	✓ (Deepstyle)	✓ (Roundstyle)	✓ (Squarestyle)	✗ (No equivalent)
Osma	✗ (No equivalent)	✗ (Stormline)	✓ (Deepline)	✓ (Roundline)	✗ (Squareline)	✗ (Mini-fit)
Polypipe	✗ (No equivalent)	✗ (Sovereign)	✓ (Polyflow)	✓	✓	✗ (Half Round)
Polypipe Terrain	✗ (No equivalent)	✗ (Omega)	✗ (Rapidflow)	✗ (Crescent)	✗ (Corniche)	✗ (No equivalent)
Marley	✗ (No equivalent)	✗ (Classic)	✓ (Deepflow)	✓ (Clipmaster)	✗ (Flowline)	✗ (Miniline)
Hunter	✗ (No equivalent)	✗ (Regency)	✓ (125)	✓	✓ (Squareflo)	✗ (Half Round)
Marshall Tufflex	✓ (Xstream)	✗ (Universal Plus)	✓ (Universal XL)	✓	✓	✗ (No equivalent)

The above is a guide only for connection to existing fitted product.
We recommend that you do not mix systems if at all possible.

Transport, Handling and Storage

FloPlast PVC-U pipes and gutters are supplied in secure bales bound with straps within timber frames, **FloPlast** recommend that movement of bales is carried out by fork lift or other mechanical device using webbing or rope strings.

The bales may be stacked up to a maximum of three high, providing that the timber frames are placed on each other.

Fittings are generally supplied in plastic bags and should be stored away from direct sunlight. If they have to be stored outside, the bags should be opened to prevent temperature build-up.

Terms and Conditions of Sale

Goods are sold subject to our Standard Terms and Conditions of Sale, copies of which are available upon request. **FloPlast Limited** reserve the right to modify or extend any product range or published information without prior notice.

